

✓ NANNINGS-vanVUUREN SALES

Turf Tick Products BV



Lifting mast see-through model



HMD 340/2500



HMD 340/2500

- Two part (duplo) lifting mast
- Heavy duty slide together U profiles
- Equipped with two double-action lifting cylinders and two chains
- With category II three-point linkage as standard
- Also available as a solid construction on the front of the tractor
- Mast width 770 mm
- Fork carriage width 1200 mm (FEM II)
- Fork length 1190 mm (foldaway)
- Adjustable fork width
- Lifting capacity calculated at 180 bar
- Drive-through height calculated with lower hitch point height 300 mm above the ground
- With wagon drawbar
- Complete with hydraulic hoses and quick connectors

Tractor specifications desired for solid construction of the lifting mast on the front of the tractor.

This type of lifting mast is not suitable in combination with the forward tipping box rotator K80/K85.

Type	Lift height	Lifting capacity	Headroom	Weight
HMD 200/1600	2.000 mm	1.600 kg	1.900 mm	375 kg
HMD 240/1600	2.400 mm	1.600 kg	2.100 mm	390 kg
HMD 280/1600	2.800 mm	1.600 kg	2.300 mm	405 kg
HMD 240/2000	2.400 mm	2.000 kg	2.100 mm	525 kg
HMD 280/2000	2.800 mm	2.000 kg	2.300 mm	625 kg
HMD 240/2500	2.400 mm	2.500 kg	2.100 mm	615 kg
HMD 280/2500	2.800 mm	2.500 kg	2.300 mm	655 kg
HMD 340/2500	3.400 mm	2.500 kg	2.600 mm	690 kg
HMD 400/2500	4.000 mm	2.500 kg	2.900 mm	725 kg

* (-/- forks), on request

Options

Solid construction of liftingmast on front of the tractor instead of three-point (Type V)

Accessories lifting masts

[Click here](#)